

The Largest Manufacturer and #1 Seller of Gutter Machines in the USA



Polyurethane Drive Train

- 3 station polyurethane drive train integral to forming rollers
- Eliminates slippage from cold weather and condensation
- Rollform a broad range of materials (aluminum, copper, steel)

Structural Steel Frame

■ Welded tubular frame

Chrome Plates 416 Stainless Steel Radius Forming Rollers

- Free-floating rollers produce less pressure and more product uniformity
- Aluminum forming roller (reduces machine weight)

Modular Turnstile Upright System

Transfer bars (ease of coil loading)

ROCK SOLID GUARANTEE: 3-YEARS Parts & Labor/Mechanical • 1-YEAR Parts & Labor/Electrical

www.GutterSupply.com

935 Campus Dr., Mundelein, IL 60060 • E-mail sales@guttersupply.com

Phone (847) 283-0006 • Toll-free (888) 909-RAIN







Manufacturing the Best Built to Stand the Test



6" Half-Round G2 Seamless Rollformer

SPECIFICATIONS

Power 1½ HP, 110 volt, single phase, 18 ampere, totally enclosed fan cooled (T.E.F.C.) motor		Dimensions Length – 162" (411.48 cm) Height – 51" (129.54 cm) Width – 33" (83.82 cm)
Weight Approximately 1,753 lbs. (795.147 kg)		Drive Powered polyurethane drive rollers via chains and sprockets
Shear Front pull guillotine		Speed Approximately 35 feet per minute
Controls Push button entry and exit end controls with "jog" feature		Options Machine mount cradles Additional runout support stands CE Certified wiring Additional turnstiles Additional spools Trailer riser pad
Recommended Materials Maximum width 11.750" (29.845 cm) or 11.875" (30.16 cm)		
Material Aluminum Copper Painted Steel Galvalume	Maximum Gauge .032 16/20 oz. 1/2-3/4 hard 24 24	

www.GutterSupply.com

935 Campus Dr. Mundelein, Illinois 60060 E-mail sales@guttersupply.com Phone (847) 283-0006 Toll-free (888) 909-RAIN



