

The Largest Manufacturer and #1 Seller of Gutter Machines in the USA



Polyurethane Drive Train

- Eliminates the need to load coil prior to transportation (less material waste)
- Eliminates slippage from cold weather and condensation

.002 Hard Chrome Plated Steel Forming Rollers

- Rollforms all recommended materials with minimal or no adjustment
- Free-floating forming rollers produce less pressure and allow for more product uniformity

Electrical and Control System

- Push button entry and exit end controls with safety wiring and "jog" feature
- · 3/4 HP, 110 volt, single phase motor, 11 ampere

Structural Steel Frame

Welded tubular frame

Modular Turnstile Upright System & Transfer Bars

Transfer bars (ease of coil loading)

ROCK SOLID GUARANTEE:

3-YEARS Parts & Labor/Mechanical

1-YEAR Parts & Labor/Electrical

www.GutterSupply.com

935 Campus Dr., Mundelein, IL 60060 • E-mail sales@guttersupply.com Phone (847) 283-0006 Toll-free (888) 909-RAIN



N MAN

Junior 5"





Manufacturing the Best Built to Stand the Test



SPECIFICATIONS

Power 3/4 HP, 110 volt, single phase, 11 ampere, totally enclosed fan cooled (T.E.F.C.) motor	Dimensions Length – 85" (215.9 cm) Height – 33" (83.8 cm) Width – 24" (61.0 cm)
Weight Approximately 922 lbs. (419.1 kg) with two full size cradles	Drive Powered polyurethane drive rollers via chains and sprockets
Shear Front pull guillotine	Speed Approximately 35 feet per minute
Controls Push button entry and exit end controls with "jog" feature	Options Machine mount cradles Additional runout support stands Smart Machine (automated length control) CE Certified wiring Additional turnstiles Additional spools Trailer riser pad
Recommended Materials Maximum width 11 3/4" to 12" Material Maximum gauge Aluminum .032 Copper 16 oz.–20 oz. 3/4 hard	

www.GutterSupply.com

935 Campus Dr., Mundelein, IL 60060 ■ E-mail sales@guttersupply.com Phone (847) 283-0006 ■ Toll-free (888) 909-RAIN



